


D965 TRANSISTOR (NPN)

FEATURES

- Audio Amplifier
- Flash Unit of Camera
- Switching Circuit



ORDERING INFORMATION

| Part Number | Package | Packing Method | Pack Quantity |
|-------------|---------|----------------|---------------|
| D965 | TO-92 | Bulk | 1000pcs/Bag |
| D965-TA | TO-92 | Tape | 2000pcs/Box |

MAXIMUM RATINGS (T_a=25°C unless otherwise noted)

| Symbol | Parameter | Value | Unit |
|-----------------------------------|--|----------|-------|
| V _{CB0} | Collector-Base Voltage | 42 | V |
| V _{CEO} | Collector-Emitter Voltage | 22 | V |
| V _{EBO} | Emitter-Base Voltage | 6 | V |
| I _C | Collector Current -Continuous | 5 | A |
| P _D | Collector Power Dissipation | 750 | mW |
| R _{θJA} | Thermal Resistance from Junction to Ambient | 166.7 | °C /W |
| T _J , T _{stg} | Operation Junction and Storage Temperature Range | -55~+150 | °C |

$T_a=25\text{ }^\circ\text{C}$ unless otherwise specified

| Parameter | Symbol | Test conditions | MIN | TYP | MAX | UNIT |
|--------------------------------------|---------------|---|-----|-----|------|---------------|
| Collector-base breakdown voltage | $V_{(BR)CBO}$ | $I_C=0.1\text{mA}, I_E=0$ | 42 | | | V |
| Collector-emitter breakdown voltage | $V_{(BR)CEO}$ | $I_C=1\text{mA}, I_B=0$ | 22 | | | V |
| Emitter-base breakdown voltage | $V_{(BR)EBO}$ | $I_E=10\mu\text{A}, I_C=0$ | 6 | | | V |
| Collector cut-off current | I_{CBO} | $V_{CB}=30\text{V}, I_E=0$ | | | 0.1 | μA |
| Emitter cut-off current | I_{EBO} | $V_{EB}=6\text{V}, I_C=0$ | | | 0.1 | μA |
| DC current gain | $h_{FE(1)}$ | $V_{CE}=2\text{V}, I_C=0.15\text{mA}$ | 150 | | | |
| | $h_{FE(2)}$ | $V_{CE}=2\text{V}, I_C=500\text{mA}$ | 340 | | 2000 | |
| | $h_{FE(3)}$ | $V_{CE}=2\text{V}, I_C=2\text{A}$ | 150 | | | |
| Collector-emitter saturation voltage | $V_{CE(sat)}$ | $I_C=3000\text{mA}, I_B=100\text{mA}$ | | | 0.35 | V |
| Transition frequency | f_T | $V_{CE}=6\text{V}, I_C=50\text{mA}, f=30\text{MHz}$ | | 150 | | MHz |

CLASSIFICATION OF $h_{FE(2)}$

| Rank | R | T | V |
|-------|---------|---------|----------|
| Range | 340-600 | 560-950 | 900-2000 |

Static Characteristic

