


FMMT720 TRANSISTOR (PNP)

FEATURE

- Switching transistor
- Extremely low saturation voltage
- Complementary NPN type: FMMT619

APPLICATION

- Gate Driving MOSFETs and IGBTs
- DC-DC converters
- Charging circuit
- Power switches



MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CB0}	Collector-Base Voltage	-40	V
V_{CE0}	Collector-Emitter Voltage	-40	V
V_{EB0}	Emitter-Base Voltage	-5	V
I_B	Base Current	-0.5	A
I_{c^*}	Collector Current -Continuous	-1.5	A
I_{CM}	Peak Pulse Current	-4	A
P_C	Total Collector Dissipation	350	mW
$R_{\theta JA}$	Thermal Resistance from Junction to Ambient	357	$^{\circ}\text{C}/\text{W}$
T_J, T_{stg}	Operation Junction and Storage Temperature Range	-55~+150	$^{\circ}\text{C}$

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C = -100\mu A, I_E = 0$	-40			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}^*$	$I_C = -10mA, I_B = 0$	-40			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E = -100\mu A, I_C = 0$	-5			V
Collector cut-off current	I_{CBO}	$V_{CB} = -35V, I_E = 0$			-0.1	μA
Collector cut-off current	I_{CES}	$V_{CE} = -35V, V_{BE} = 0$			-0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB} = -4V, I_C = 0$			-0.1	μA
DC current gain	$h_{FE(1)}^*$	$V_{CE} = -2V, I_C = -10mA$	300			
	$h_{FE(2)}^*$	$V_{CE} = -2V, I_C = -100mA$	300			
	$h_{FE(3)}^*$	$V_{CE} = -2V, I_C = -1A$	180			
	$h_{FE(4)}^*$	$V_{CE} = -2V, I_C = -1.5A$	60			
	$h_{FE(5)}^*$	$V_{CE} = -2V, I_C = -3A$	12			
Collector-emitter saturation voltage	$V_{CE(sat)(1)}^*$	$I_C = -0.1A, I_B = -10mA$			-40	mV
	$V_{CE(sat)(2)}^*$	$I_C = -1A, I_B = -50mA$			-220	mV
	$V_{CE(sat)(3)}^*$	$I_C = -1.5A, I_B = -100mA$			-330	mV
Base-emitter saturation voltage	$V_{BE(sat)}^*$	$I_C = -1.5A, I_B = -75mA$			-1	V
Base-emitter voltage	$V_{BE(on)}^*$	$V_{CE} = -2V, I_C = -1.5A$			-1	V
Transition frequency	f_T	$V_{CE} = -10V, I_C = -50mA, f = 100MHz$	150			MHz
Collector output capacitance	C_{ob}	$V_{CB} = -10V, f = 1MHz$			25	pF
Turn-on Time	$t_{(on)}$	$V_{CC} = -15V, I_C = -0.75A, I_{B1} = I_{B2} = -15mA$		40		ns
Turn-off Time	$t_{(off)}$			435		ns

*Measured under pulse conditions . Pulse width =300 μs . Duty cycle \leq 2%.

Static Characteristic
