


## KSA539 TRANSISTOR (PNP)

### FEATURES

- Low Saturation Medium Current Application
- Complement to KSC815



### ORDERING INFORMATION

Part Number	Package	Packing Method	Pack Quantity
KSA539	TO-92	Bulk	1000pcs/Bag
KSA539-TA	TO-92	Tape	2000pcs/Box

### MAXIMUM RATINGS ( $T_a=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Unit
$V_{CBO}$	Collector-Base Voltage	-60	V
$V_{CEO}$	Collector-Emitter Voltage	-45	V
$V_{EBO}$	Emitter-Base Voltage	-5	V
$I_C$	Collector Current	-0.2	A
$P_c$	Collector Power Dissipation	400	mW
$R_{\theta JA}$	Thermal Resistance From Junction To ambient	312	°C/W
$T_J, T_{stg}$	Operation Junction and Storage Temperature Range	-55~+150	°C

**T<sub>a</sub>=25 °C unless otherwise specified**

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
<b>Collector-base breakdown voltage</b>	V <sub>(BR)CBO</sub>	I <sub>C</sub> =- 0.1mA, I <sub>E</sub> =0	-60			V
<b>Collector-emitter breakdown voltage</b>	V <sub>(BR)CEO</sub>	I <sub>C</sub> =-10mA, I <sub>B</sub> =0	-45			V
<b>Emitter-base breakdown voltage</b>	V <sub>(BR)EBO</sub>	I <sub>E</sub> =-0.01mA, I <sub>C</sub> =0	-5			V
<b>Collector cut-off current</b>	I <sub>CBO</sub>	V <sub>CB</sub> =-45V, I <sub>E</sub> =0			-0.1	µA
<b>Emitter cut-off current</b>	I <sub>EBO</sub>	V <sub>EB</sub> =-3V, I <sub>C</sub> =0			-0.1	µA
<b>DC current gain</b>	h <sub>FE</sub>	V <sub>CE</sub> =-1V, I <sub>C</sub> =-50mA	40	240		
<b>Collector-emitter saturation voltage</b>	V <sub>CE(sat)</sub>	I <sub>C</sub> =-150mA, I <sub>B</sub> =-15mA			-0.5	V
<b>Base-emitter saturation voltage</b>	V <sub>BE(sat)</sub>	I <sub>C</sub> =-150mA, I <sub>B</sub> =-15mA			-1.2	V
<b>Base-emitter voltage</b>	V <sub>BE</sub>	V <sub>CE</sub> =-1V, I <sub>C</sub> =-10mA	-0.6		-0.9	V

#### CLASSIFICATION OF h<sub>FE</sub>

RANK	R	O	Y
RANGE	40-80	70-140	120-240