


## M8550 TRANSISTOR (PNP)

### FEATURES

- Power Dissipation



### ORDERING INFORMATION

Part Number	Package	Packing Method	Pack Quantity
M8550	TO-92	Bulk	1000pcs/Bag
M8550-TA	TO-92	Tape	2000pcs/Box

### MAXIMUM RATINGS (T<sub>a</sub>=25°C unless otherwise noted)

Symbol	Parameter	Value	Unit
V <sub>CB0</sub>	Collector-Base Voltage	-40	V
V <sub>CEO</sub>	Collector-Emitter Voltage	-25	V
V <sub>EBO</sub>	Emitter-Base Voltage	-6	V
I <sub>C</sub>	Collector Current -Continuous	-800	mA
P <sub>C</sub>	Collector Power Dissipation	625	mW
T <sub>J</sub> , T <sub>stg</sub>	Operation Junction and Storage Temperature Range	-55~+150	°C

$T_a=25\text{ }^\circ\text{C}$  unless otherwise specified

Parameter	Symbol	Test conditions	Min	Max	Unit
Collector-base breakdown voltage	$V(BR)_{CBO}$	$I_C = -100\mu A, I_E = 0$	-40		V
Collector-emitter breakdown voltage	$V(BR)_{CEO}^*$	$I_C = -0.1mA, I_B = 0$	-25		V
Emitter-base breakdown voltage	$V(BR)_{EBO}$	$I_E = -100\mu A, I_C = 0$	-6		V
Collector cut-off current	$I_{CBO}$	$V_{CB} = -35V, I_E = 0$		-0.1	$\mu A$
Collector cut-off current	$I_{CEO}$	$V_{CE} = -20V, I_B = 0$		-0.1	$\mu A$
DC current gain	$h_{FE(1)}$	$V_{CE} = -1V, I_C = -5mA$	45		
	$h_{FE(2)}$	$V_{CE} = -1V, I_C = -100mA$	80	400	
	$h_{FE(3)}$	$V_{CE} = -1V, I_C = -800mA$	40		
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = -800mA, I_B = -80mA$		-0.5	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C = -800mA, I_B = -80mA$		-1.2	V
Transition frequency	$f_T$	$V_{CE} = -6V, I_C = -20mA$ $f = 30MHz$	150		MHz

\*Pulse Test: pulse width  $\leq 300\mu s$ , duty cycle  $\leq 2\%$ .

#### CLASSIFICATION OF $h_{FE(2)}$

Rank	B	C	D	D3
Range	80-160	120-200	160-300	300-400

# Typical Characteristics

# M8550

