


MPS2222 TRANSISTOR (NPN)

FEATURES

- General Purpose Switching and Amplification



ORDERING INFORMATION

| Part Number | Package | Packing Method | Pack Quantity |
|-------------|---------|----------------|---------------|
| MPS2222 | TO-92 | Bulk | 1000pcs/Bag |
| MPS2222-TA | TO-92 | Tape | 2000pcs/Box |

MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

| Symbol | Parameter | Value | Unit |
|-----------------|--|----------|----------------------|
| V_{CBO} | Collector-Base Voltage | 60 | V |
| V_{CEO} | Collector-Emitter Voltage | 30 | V |
| V_{EBO} | Emitter-Base Voltage | 5 | V |
| I_C | Collector Current -Continuous | 0.6 | A |
| P_C | Collector Power Dissipation | 625 | mW |
| $R_{\theta JA}$ | Thermal Resistance From Junction To Ambient | 200 | $^{\circ}\text{C/W}$ |
| T_J, T_{stg} | Operation Junction and Storage Temperature Range | -55~+150 | $^{\circ}\text{C}$ |

$T_a=25\text{ }^\circ\text{C}$ unless otherwise specified

| Parameter | Symbol | Test conditions | Min | Typ | Max | Unit |
|--------------------------------------|-----------------|---|-----|-----|------|---------------|
| Collector-base breakdown voltage | $V_{(BR)CBO}$ | $I_C=0.01\text{mA}, I_E=0$ | 60 | | | V |
| Collector-emitter breakdown voltage | $V_{(BR)CEO}$ | $I_C=10\text{mA}, I_B=0$ | 30 | | | V |
| Emitter-base breakdown voltage | $V_{(BR)EBO}$ | $I_E=0.01\text{mA}, I_C=0$ | 5 | | | V |
| Collector cut-off current | I_{CBO} | $V_{CB}=50\text{V}, I_E=0$ | | | 0.01 | μA |
| Collector cut-off current | I_{CEX} | $V_{CE}=60\text{V}, V_{EB(off)}=3\text{V}$ | | | 0.01 | μA |
| Emitter cut-off current | I_{EBO} | $V_{EB}=3\text{V}, I_C=0$ | | | 0.1 | μA |
| DC current gain | $h_{FE(1)}$ * | $V_{CE}=10\text{V}, I_C=150\text{mA}$ | 100 | | 300 | |
| | $h_{FE(2)}$ | $V_{CE}=10\text{V}, I_C=0.1\text{mA}$ | 35 | | | |
| | $h_{FE(3)}$ | $V_{CE}=10\text{V}, I_C=500\text{mA}$ | 30 | | | |
| Collector-emitter saturation voltage | $V_{CE(sat)}$ * | $I_C=500\text{mA}, I_B=50\text{mA}$ | | | 1 | V |
| Base-emitter saturation voltage | $V_{BE(sat)}$ * | $I_C=500\text{mA}, I_B=50\text{mA}$ | | | 2 | V |
| Collector output capacitance | C_{ob} | $V_{CB}=10\text{V}, I_E=0, f=100\text{MHz}$ | | | 8 | pF |
| Transition frequency | f_T | $V_{CE}=20\text{V}, I_C=20\text{mA}, f=100\text{MHz}$ | 250 | | | MHz |
| Delay time | t_d | $V_{CC}=30\text{V}, V_{BE(off)}=-0.5\text{V}$ | | | 10 | nS |
| Rise time | t_r | $I_C=150\text{mA}, I_{B1}=15\text{mA}$ | | | 25 | nS |
| Storage time | t_s | $V_{CC}=30\text{V}, I_C=150\text{mA}$ | | | 225 | nS |
| Fall time | t_f | $I_{B1}=I_{B2}=15\text{mA}$ | | | 60 | nS |

 *Pulse test: pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2.0\%$.