


PH2369 TRANSISTOR (NPN)

FEATURES

- Power Dissipation



ORDERING INFORMATION

Part Number	Package	Packing Method	Pack Quantity
PH2369	TO-92	Bulk	1000pcs/Bag
PH2369-TA	TO-92	Tape	2000pcs/Box

MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CB0}	Collector-Base Voltage	40	V
V_{CEO}	Collector-Emitter Voltage	15	V
V_{EBO}	Emitter-Base Voltage	4.5	V
I_C	Collector Current –Continuous	0.2	A
P_C	Collector Power Dissipation	500	mW
T_J, T_{stg}	Operation Junction and Storage Temperature Range	-55-150	$^{\circ}\text{C}$

$T_a=25^\circ\text{C}$ unless otherwise specified

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=100\mu\text{A}, I_E=0$	40			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=10\text{mA}, I_B=0$	15			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=10\mu\text{A}, I_C=0$	4.5			V
Collector cut-off current	I_{CBO}	$V_{CB}=20\text{V}, I_E=0$			0.4	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=4\text{V}, I_C=0$			0.1	μA
DC current gain	h_{FE1}	$V_{CE}=1\text{V}, I_C=10\text{mA}$	40		120	
	h_{FE2}	$V_{CE}=2\text{V}, I_C=100\text{mA}$	20			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=10\text{mA}, I_B=1\text{mA}$			0.25	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C=10\text{mA}, I_B=1\text{mA}$	0.7		0.85	V
Transition frequency	f_T	$V_{CE}=10\text{V}, I_C=10\text{mA}$ $f=100\text{MHz}$	500			MHz
Collector capacitance	C_c	$V_{CB}=5\text{V}, I_E=0, f=1\text{MHz}$			4	pF
Emitter capacitance	C_e	$V_{EB}=1\text{V}, I_E=0, f=1\text{MHz}$			4.5	pF
Turn-on time	t_{on}	$V_{CC}=3\text{V}, I_C=10\text{mA},$ $I_{B1}=3\text{mA}$			10	nS
Turn-off time	t_{off}				20	nS