


SBD1045LCT、SBDF1045LCT SCHOTTKY BARRIER RECTIFIER

MAIN CHARACTERISTICS

I_o	10 (2×5) A
V_{RRM}	45 V
T_j	150 °C
$V_F(\text{typ})$	0.40V (@Tj=125°C)



MAXIMUM RATINGS ($T_a=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	SBD		Unit
		1045LCT	F1045LCT	
V_{RRM}	Peak repetitive reverse voltage			
V_{RWM}	Working peak reverse voltage		45	V
V_R	DC blocking voltage			
$V_{R(\text{RMS})}$	RMS reverse voltage		31.5	V
I_o	Average rectified output current		10	A
I_{FSM}	Non-Repetitive peak forward surge current (8.3ms half sine wave)		120	A
$R_{\Theta JC}$	Thermal resistance from junction to case , $T_c=25^\circ\text{C}$	2.0	3.0	°C/W
$R_{\Theta JA}$	Thermal resistance from junction to ambient		62.5	°C/W
T_j	Junction temperature		150	°C
T_{stg}	Storage temperature		-55~+150	°C

ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse voltage	$V_{(BR)}$	$I_R=1\text{mA}$	45			V
Reverse current	I_R	$V_R=45\text{V}$	$T_j = 25^\circ\text{C}$	50	100	uA
			$T_j = 125^\circ\text{C}$	20		mA
Forward voltage	V_F	$I_F=3\text{A}$	$T_j = 25^\circ\text{C}$	0.42		V
			$T_j = 125^\circ\text{C}$	0.34		V
		$I_F=5\text{A}$	$T_j = 25^\circ\text{C}$	0.46	0.55	V
			$T_j = 125^\circ\text{C}$	0.40		V

*Pulse test: pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2.0\%$.

FIG.1: FORWARD CURRENT DERATING CURVE




FIG.2: TYPICAL FORWARD CHARACTERISTICS




FIG.3: TOTAL CAPACITANCE DERATING CURVE




FIG.4: TYPICAL REVERSE CHARACTERISTICS

