

# SBD30120TCTB、SBDF30120TCTB


SCHOTTKY BARRIER RECTIFIER

## MAIN CHARACTERISTICS

$I_o$	30 (2×15) A
$V_{RRM}$	120 V
$T_j$	150 °C
$V_{F(ty)}$	0.68V (@ $T_j=125^{\circ}\text{C}$ )

## FEATURES

- Low Power Loss, High Efficiency
- Guard Ring Die Construction for Transient Protection
- High Current Capability and Low Forward Voltage Drop



## MAXIMUM RATINGS ( $T_a=25^{\circ}\text{C}$ unless otherwise noted )

Symbol	Parameter	SBD		Unit
		30120TCTB	F30120TCTB	
$V_{RRM}$	Peak repetitive reverse voltage			
$V_{RWM}$	Working peak reverse voltage		120	V
$V_R$	DC blocking voltage			
$V_{R(RMS)}$	RMS reverse voltage	84		V
$I_o$	Average rectified output current	30		A
$I_{FSM}$	Non-Repetitive peak forward surge current (8.3ms half sine wave)	200		A
$R_{\Theta JC}$	Thermal resistance from junction to case , $T_c=25^{\circ}\text{C}$	2.0	3.0	°C/W
$R_{\Theta JA}$	Thermal resistance from junction to ambient	62.5		°C/W
$T_j$	Junction temperature	150		°C
$T_{stg}$	Storage temperature	-55~+150		°C

## ELECTRICAL CHARACTERISTICS ( $T_a=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions		Min	Typ	Max	Unit
Reverse voltage	$V_{(BR)}$	$I_R=0.1\text{mA}$		120			V
Reverse current	$I_R$	$V_R=120\text{V}$	$T_j = 25^{\circ}\text{C}$		10	100	uA
			$T_j = 125^{\circ}\text{C}$		10		mA
Forward voltage	$V_F$	$I_F=10\text{A}$	$T_j = 25^{\circ}\text{C}$		0.69		V
			$T_j = 125^{\circ}\text{C}$		0.61		V
		$I_F=15\text{A}$	$T_j = 25^{\circ}\text{C}$		0.83	0.89	V
			$T_j = 125^{\circ}\text{C}$		0.68		V

\*Pulse test: pulse width ≤300μs, duty cycle≤ 2.0%.

FIG.1: FORWARD CURRENT DERATING CURVE




FIG.2: TYPICAL FORWARD CHARACTERISTICS




FIG.3: TOTAL CAPACITANCE DERATING CURVE




FIG.4: TYPICAL REVERSE CHARACTERISTICS

