


**SBD30130TCTB、SBDF30130TCTB** SCHOTTKY BARRIER RECTIFIER  
MAIN CHARACTERISTICS

$I_o$	<b>30 (2×15) A</b>
$V_{RRM}$	<b>130 V</b>
$T_j$	<b>150 °C</b>
$V_{F(typ)}$	<b>0.68V (@Tj=125°C)</b>

**FEATURES**

- Low Power Loss,High Efficiency
- Guard Ring Die Construction for Transient Protection
- High Current Capability and Low Forward Voltage Drop



**MAXIMUM RATINGS ( T<sub>a</sub>=25°C unless otherwise noted )**

Symbol	Parameter	SBD		Unit
		30130TCTB	F30130TCTB	
$V_{RRM}$	Peak repetitive reverse voltage	130		V
$V_{RWM}$	Working peak reverse voltage			
$V_R$	DC blocking voltage			
$V_{R(RMS)}$	RMS reverse voltage	91		V
$I_o$	Average rectified output current	30		A
$I_{FSM}$	Non-Repetitive peak forward surge current (8.3ms half sine wave)	200		A
$R_{\theta Jc}$	Thermal resistance from junction to case ,Tc=25°C	2.0	3.0	°C/W
$R_{\theta JA}$	Thermal resistance from junction to ambient	62.5		°C/W
$T_j$	Junction temperature	150		°C
$T_{stg}$	Storage temperature	-55~+150		°C

**ELECTRICAL CHARACTERISTICS (T<sub>a</sub>=25°C unless otherwise specified)**

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse voltage	$V_{(BR)}$	$I_R=0.1mA$	130			V
Reverse current	$I_R$	$V_R=130V$	$T_j=25^\circ C$	10	100	uA
			$T_j=125^\circ C$	10		mA
Forward voltage	$V_F$	$I_F=10A$	$T_j=25^\circ C$	0.70		V
			$T_j=125^\circ C$	0.61		V
		$I_F=15A$	$T_j=25^\circ C$	0.84	0.89	V
			$T_j=125^\circ C$	0.68		V

\*Pulse test: pulse width ≤300μs, duty cycles ≤ 2.0%.

FIG.1: FORWARD CURRENT DERATING CURVE




FIG.2: TYPICAL FORWARD CHARACTERISTICS




FIG.3: TOTAL CAPACITANCE DERATING CURVE




FIG.4: TYPICAL REVERSE CHARACTERISTICS

