


VS7906 Three-terminal negative voltage regulator

FEATURES

- Maximum output current
 I_{OM} : 1.5 A
- Output voltage
 V_O : -6V
- Continuous total dissipation
 P_D : 1.5 W ($T_a = 25^\circ C$)



ABSOLUTE MAXIMUM RATINGS (Operating temperature range applies unless otherwise specified)

Parameter	Symbol	Value	Unit
Input Voltage	V_i	-35	V
Thermal Resistance from Junction to Air	$R_{\theta JA}$	83.3	°C/W
Operating Junction Temperature Range	T_{OPR}	-40~+125	°C
Storage Temperature Range	T_{STG}	-65~+150	°C

ELECTRICAL CHARACTERISTICS AT SPECIFIED VIRTUAL JUNCTION TEMPERATURE ($V_i = -11V$, $I_o = 500mA$, $C_i = 2.2\mu F$, $C_o = 1\mu F$, unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Output Voltage	V_o	$T_J = 25^\circ C$	-5.82	-6	-6.18	V
		$-8V \leq V_i \leq -21V$, $I_o = 5mA-1A$	-5.7	-6	-6.3	V
Load Regulation	ΔV_o	$I_o = 5mA-1.5A$, $T_J = 25^\circ C$		15	120	mV
		$I_o = 250mA-750mA$, $T_J = 25^\circ C$		5	60	mV
Line Regulation	ΔV_o	$-8V \leq V_i \leq -25V$, $T_J = 25^\circ C$		12.5	120	mV
		$-9V \leq V_i \leq -13V$, $T_J = 25^\circ C$		4	60	mV
Quiescent Current	I_q	$T_J = 25^\circ C$		1.5	2	mA
Quiescent Current Change	ΔI_q	$-8V \leq V_i \leq -25V$			1.3	mA
	ΔI_q	$5mA \leq I_o \leq 1A$			0.5	mA
Output Noise Voltage	V_N	$10Hz \leq f \leq 100KHz$, $T_J = 25^\circ C$		150		$\mu V/V_o$
Output Voltage Drift	$\Delta V_o/\Delta T$	$I_o = 5mA$		-0.4		$mV/^\circ C$
Ripple Rejection	RR	$-9V \leq V_i \leq -19V$, $f = 120Hz$	54	60		dB
Dropout Voltage	V_d	$I_o = 1A$, $T_J = 25^\circ C$		1.1		V
Peak Current	I_{pk}	$T_J = 25^\circ C$		2.1		A

* Pulse test.

TYPICAL APPLICATION

