


VS7915F Three-terminal negative voltage regulator

FEATURES

- Maximum output current
 I_{OM} : 1.5 A
- Output voltage
 V_O : -15 V
- Continuous total dissipation
 P_D : 1.5 W ($T_a = 25^\circ C$)



ABSOLUTE MAXIMUM RATINGS (Operating temperature range applies unless otherwise specified)

Parameter	Symbol	Value	Unit
Input Voltage	V_i	-35	V
Thermal Resistance from Junction to Air	$R_{\theta JA}$	83.3	°C/W
Operating Junction Temperature Range	T_{OPR}	-40~+125	°C
Storage Temperature Range	T_{STG}	-65~+150	°C

ELECTRICAL CHARACTERISTICS AT SPECIFIED VIRTUAL JUNCTION TEMPERATURE ($V_i = -23V$, $I_o = 500mA$, $C_i = 2.2\mu F$, $C_o = 1\mu F$, unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Output Voltage	V_o	$T_J = 25^\circ C$	-14.55	-15	-15.45	V
		$-17.5V \leq V_i \leq -30V$, $I_o = 5mA$	-14.25	-15	-15.75	V
Load Regulation	ΔV_o	$I_o = 5mA - 1.5A$, $T_J = 25^\circ C$		15	200	mV
		$I_o = 250mA - 750mA$, $T_J = 25^\circ C$		5	75	mV
Line Regulation	ΔV_o	$-17.5V \leq V_i \leq -30V$, $T_J = 25^\circ C$		5	100	mV
		$-20V \leq V_i \leq -26V$, $T_J = 25^\circ C$		3	50	mV
Quiescent Current	I_q	$T_J = 25^\circ C$		2	3	mA
Quiescent Current Change	ΔI_q	$-17.5V \leq V_i \leq -30V$			0.5	mA
	ΔI_q	$5mA \leq I_o \leq 1A$			0.5	mA
Output Noise Voltage	V_N	$10Hz \leq f \leq 100KHz$, $T_J = 25^\circ C$		375		$\mu V/V_o$
Output Voltage Drift	$\Delta V_o / \Delta T$	$I_o = 5mA$		-1		$mV/^\circ C$
Ripple Rejection	RR	$-18.5V \leq V_i \leq -28.5V$, $f = 120Hz$	54	60		dB
Dropout Voltage	V_d	$I_o = 1A$, $T_J = 25^\circ C$		1.1		V
Peak Current	I_{pk}	$T_J = 25^\circ C$		2.1		A

* Pulse test.

TYPICAL APPLICATION

