

Description

The VSM7N06 uses advanced trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications.

General Features


- $V_{DS} = 60V, I_D = 7A$
- $R_{DS(ON)} < 30m\Omega @ V_{GS}=10V$ (Typ: $24m\Omega$)
- $R_{DS(ON)} < 35m\Omega @ V_{GS}=4.5V$ (Typ: $27m\Omega$)
- High density cell design for ultra low $R_{DS(on)}$
- Fully characterized avalanche voltage and current
- Low gate to drain charge to reduce switching losses

Application

- Power switching application
- Hard switched and high frequency circuits
- Uninterruptible power supply



SOP-8



Schematic Diagram

Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
VSM7N06-S8	VSM7N06	SOP-8	Ø330mm	12mm	2500 units

Absolute Maximum Ratings ($T_A=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous	I_D	7	A
Drain Current-Continuous($T_C=100^\circ C$)	$I_D (100^\circ C)$	5	A
Pulsed Drain Current	I_{DM}	40	A
Maximum Power Dissipation	P_D	2.1	W
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 To 150	°C

Thermal Characteristic

Thermal Resistance, Junction-to-Ambient ^(Note 2)	$R_{\theta JA}$	60	°C/W
---	-----------------	----	------

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)


Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_D=250\mu\text{A}$	60	69	-	V
Zero Gate Voltage Drain Current	I_{DSS}	$\text{V}_{\text{DS}}=60\text{V}, \text{V}_{\text{GS}}=0\text{V}$	-	-	1	μA
Gate-Body Leakage Current	I_{GSS}	$\text{V}_{\text{GS}}=\pm20\text{V}, \text{V}_{\text{DS}}=0\text{V}$	-	-	±100	nA
On Characteristics ^(Note 3)						
Gate Threshold Voltage	$\text{V}_{\text{GS(th)}}$	$\text{V}_{\text{DS}}=\text{V}_{\text{GS}}, \text{I}_D=250\mu\text{A}$	1.0	1.4	2.0	V
Drain-Source On-State Resistance	$\text{R}_{\text{DS(ON)}}$	$\text{V}_{\text{GS}}=10\text{V}, \text{I}_D=7\text{A}$		24	30	$\text{m}\Omega$
		$\text{V}_{\text{GS}}=4.5\text{V}, \text{I}_D=6\text{A}$		27	35	$\text{m}\Omega$
Forward Transconductance	g_{FS}	$\text{V}_{\text{DS}}=5\text{V}, \text{I}_D=7\text{A}$		20	-	S
Dynamic Characteristics ^(Note 4)						
Input Capacitance	C_{iss}	$\text{V}_{\text{DS}}=25\text{V}, \text{V}_{\text{GS}}=0\text{V}, \text{F}=1.0\text{MHz}$		1920		PF
Output Capacitance	C_{oss}			155		PF
Reverse Transfer Capacitance	C_{rss}			116		PF
Switching Characteristics ^(Note 4)						
Turn-on Delay Time	$t_{\text{d(on)}}$	$\text{V}_{\text{DS}}=30\text{V}, \text{R}_L=4.7\Omega$ $\text{V}_{\text{GS}}=10\text{V}, \text{R}_{\text{GEN}}=3\Omega$	-	8	-	nS
Turn-on Rise Time	t_r		-	5	-	nS
Turn-Off Delay Time	$t_{\text{d(off)}}$		-	29	-	nS
Turn-Off Fall Time	t_f		-	6	-	nS
Total Gate Charge	Q_g	$\text{V}_{\text{DS}}=30\text{V}, \text{I}_D=7\text{A}, \text{V}_{\text{GS}}=10\text{V}$	-	50	-	nC
Gate-Source Charge	Q_{gs}		-	8	-	nC
Gate-Drain Charge	Q_{gd}		-	16	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage ^(Note 3)	V_{SD}	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_s=7\text{A}$	-	-	1.2	V
Diode Forward Current ^(Note 2)	I_s		-	-	7	A
Reverse Recovery Time	t_{rr}	$\text{TJ} = 25^\circ\text{C}, \text{I}_F = 7\text{A}$ $d\text{i}/dt = 100\text{A}/\mu\text{s}$ ^(Note 3)	-	35	-	nS
Reverse Recovery Charge	Q_{rr}		-	43	-	nC
Forward Turn-On Time	t_{on}	Intrinsic turn-on time is negligible (turn-on is dominated by LS+LD)				

Notes:


1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, $t \leq 10$ sec.
3. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.
4. Guaranteed by design, not subject to production

Test Circuit


1) E_{AS} test Circuits



2) Gate charge test Circuit



3) Switch Time Test Circuit



Typical Electrical and Thermal Characteristics (Curves)




Figure 1 Output Characteristics




Figure 4 Rdson-JunctionTemperature




Figure 2 Transfer Characteristics




Figure 5 Gate Charge




Figure 3 Rdson- Drain Current









Figure 6 Source- Drain Diode Forward


Figure 7 Capacitance vs Vds

Figure 9 Power De-rating

Figure 8 Safe Operation Area

Figure 10 Current De-rating

Figure 11 Normalized Maximum Transient Thermal Impedance