

Description


The VST06N040 uses **Super Trench** technology that is uniquely optimized to provide the most efficient high frequency switching performance. Both conduction and switching power losses are minimized due to an extremely low combination of $R_{DS(ON)}$ and Q_g . This device is ideal for high-frequency switching and synchronous rectification.

General Features

- $V_{DS} = 60V, I_D = 20A$
- $R_{DS(ON)} = 4.0m\Omega$ (typical) @ $V_{GS} = 10V$
- $R_{DS(ON)} = 4.6m\Omega$ (typical) @ $V_{GS} = 4.5V$
- Excellent gate charge $\times R_{DS(on)}$ product(FOM)
- Very low on-resistance $R_{DS(on)}$
- 150 °C operating temperature
- Pb-free lead plating
- 100% UIS tested

Application

- DC/DC Converter
- Ideal for high-frequency switching and synchronous rectification



SOP-8

Schematic Diagram

Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
VST06N040-S8	VST06N040	SOP-8	Ø330mm	12mm	2500 units

Absolute Maximum Ratings ($T_A = 25^\circ C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous	I_D	20	A
Drain Current-Continuous($T_C = 100^\circ C$)	$I_D (100^\circ C)$	14	A
Pulsed Drain Current	I_{DM}	130	A
Maximum Power Dissipation	P_D	3.5	W
Single pulse avalanche energy (Note 5)	E_{AS}	320	mJ
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 To 150	°C

Thermal Characteristic

Thermal Resistance, Junction-to-Ambient ^(Note 2)	$R_{\theta A}$	36	°C/W
---	----------------	----	------

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)


Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_D=250 \mu\text{A}$	60	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	$\text{V}_{\text{DS}}=60\text{V}, \text{V}_{\text{GS}}=0\text{V}$	-	-	1	μA
Gate-Body Leakage Current	I_{GSS}	$\text{V}_{\text{GS}}=\pm 20\text{V}, \text{V}_{\text{DS}}=0\text{V}$	-	-	± 100	nA
On Characteristics (Note 3)						
Gate Threshold Voltage	$\text{V}_{\text{GS(th)}}$	$\text{V}_{\text{DS}}=\text{V}_{\text{GS}}, \text{I}_D=250 \mu\text{A}$	1.0	1.7	2.4	V
Drain-Source On-State Resistance	$\text{R}_{\text{DS(ON)}}$	$\text{V}_{\text{GS}}=10\text{V}, \text{I}_D=20\text{A}$	-	4.0	4.5	$\text{m}\Omega$
		$\text{V}_{\text{GS}}=4.5\text{V}, \text{I}_D=18\text{A}$	-	4.6	5.4	$\text{m}\Omega$
Forward Transconductance	g_{FS}	$\text{V}_{\text{DS}}=5\text{V}, \text{I}_D=20\text{A}$	35	-	-	S
Dynamic Characteristics (Note 4)						
Input Capacitance	C_{iss}	$\text{V}_{\text{DS}}=30\text{V}, \text{V}_{\text{GS}}=0\text{V}, \text{F}=1.0\text{MHz}$	-	4000	-	PF
Output Capacitance	C_{oss}		-	680	-	PF
Reverse Transfer Capacitance	C_{rss}		-	23	-	PF
Switching Characteristics (Note 4)						
Turn-on Delay Time	$t_{\text{d(on)}}$	$\text{V}_{\text{DD}}=30\text{V}, \text{R}_L=1.7 \Omega$ $\text{V}_{\text{GS}}=10\text{V}, \text{R}_G=3 \Omega$	-	11	-	nS
Turn-on Rise Time	t_r		-	5	-	nS
Turn-Off Delay Time	$t_{\text{d(off)}}$		-	56	-	nS
Turn-Off Fall Time	t_f		-	12	-	nS
Total Gate Charge	Q_g	$\text{V}_{\text{DS}}=30\text{V}, \text{I}_D=20\text{A}, \text{V}_{\text{GS}}=10\text{V}$	-	67	-	nC
Gate-Source Charge	Q_{gs}		-	12	-	nC
Gate-Drain Charge	Q_{gd}		-	8.5	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage (Note 3)	V_{SD}	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_s=20\text{A}$	-	-	1.2	V
Diode Forward Current (Note 2)	I_s		-	-	20	A
Reverse Recovery Time	t_{rr}	$\text{T}_J = 25^\circ\text{C}, \text{I}_F = \text{I}_s$ $d\text{i}/dt = 100\text{A}/\mu\text{s}$ (Note 3)	-	48	-	nS
Reverse Recovery Charge	Q_{rr}		-	60	-	nC

Notes:


1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, $t \leqslant 10$ sec.
3. Pulse Test: Pulse Width $\leqslant 300 \mu\text{s}$, Duty Cycle $\leqslant 2\%$.
4. Guaranteed by design, not subject to production
5. EAS condition : $\text{T}_J=25^\circ\text{C}, \text{V}_{\text{DD}}=50\text{V}, \text{V}_{\text{G}}=10\text{V}, \text{L}=0.5\text{mH}, \text{R}_G=25 \Omega$

Test Circuit


1) E_{AS} test Circuit



2) Gate charge test Circuit



3) Switch Time Test Circuit



Typical Electrical and Thermal Characteristics




Figure 1 Output Characteristics




Figure 4 Rdson-Junction Temperature




Figure 2 Transfer Characteristics




Figure 5 Gate Charge




Figure 3 Rdson- Drain Current









Figure 6 Source- Drain Diode Forward


Figure 7 Capacitance vs Vds

Figure 9 Power De-rating

Figure 8 Safe Operation Area

Figure 10 Current De-rating

Figure 11 Normalized Maximum Transient Thermal Impedance