

## Description

The VST15N058 uses **Super Trench** technology that is uniquely optimized to provide the most efficient high frequency switching performance. Both conduction and switching power losses are minimized due to an extremely low combination of  $R_{DS(ON)}$  and  $Q_g$ . This device is ideal for high-frequency switching and synchronous rectification.

## General Features


- $V_{DS} = 150V, I_D = 140A$
- $R_{DS(ON)} = 5.8m\Omega$ , typical @  $V_{GS} = 10V$
- Excellent gate charge  $\times R_{DS(on)}$  product(FOM)
- Very low on-resistance  $R_{DS(on)}$
- 175 °C operating temperature
- Pb-free lead plating
- 100% UIS tested

## Application

- DC/DC Converter
- Ideal for high-frequency switching and synchronous rectification



TO-220C



Schematic Diagram

## Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
VST15N058-TC	VST15N058	TO-220C	-	-	-

## Absolute Maximum Ratings ( $T_c=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	$V_{DS}$	150	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Drain Current-Continuous	$I_D$	140	A
Drain Current-Continuous( $T_c=100^\circ C$ )	$I_D (100^\circ C)$	100	A
Pulsed Drain Current	$I_{DM}$	560	A
Maximum Power Dissipation	$P_D$	320	W
Derating factor		2.1	W/°C
Single pulse avalanche energy <sup>(Note 5)</sup>	$E_{AS}$	1296	mJ
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 To 175	°C

## Thermal Characteristic

Thermal Resistance, Junction-to-Case <sup>(Note 2)</sup>	$R_{\theta JC}$	0.47	°C/W
--	-----------------	------	------

**Electrical Characteristics ( $T_c=25^\circ\text{C}$  unless otherwise noted)**


Parameter	Symbol	Condition	Min	Typ	Max	Unit
<b>Off Characteristics</b>						
Drain-Source Breakdown Voltage	$\text{BV}_{\text{DSS}}$	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_{\text{D}}=250\mu\text{A}$	150	-	-	V
Zero Gate Voltage Drain Current	$\text{I}_{\text{DSS}}$	$\text{V}_{\text{DS}}=150\text{V}, \text{V}_{\text{GS}}=0\text{V}$	-	-	1	$\mu\text{A}$
Gate-Body Leakage Current	$\text{I}_{\text{GSS}}$	$\text{V}_{\text{GS}}=\pm 20\text{V}, \text{V}_{\text{DS}}=0\text{V}$	-	-	$\pm 100$	nA
<b>On Characteristics</b> (Note 3)						
Gate Threshold Voltage	$\text{V}_{\text{GS}(\text{th})}$	$\text{V}_{\text{DS}}=\text{V}_{\text{GS}}, \text{I}_{\text{D}}=250\mu\text{A}$	2.0	3.0	4.0	V
Drain-Source On-State Resistance	$\text{R}_{\text{DS}(\text{ON})}$	$\text{V}_{\text{GS}}=10\text{V}, \text{I}_{\text{D}}=70\text{A}$	-	5.8	6.5	$\text{m}\Omega$
Forward Transconductance	$\text{g}_{\text{FS}}$	$\text{V}_{\text{DS}}=10\text{V}, \text{I}_{\text{D}}=70\text{A}$	70	-	-	S
<b>Dynamic Characteristics</b> (Note 4)						
Input Capacitance	$\text{C}_{\text{iss}}$	$\text{V}_{\text{DS}}=75\text{V}, \text{V}_{\text{GS}}=0\text{V}, \text{F}=1.0\text{MHz}$	-	5500	7150	PF
Output Capacitance	$\text{C}_{\text{oss}}$		-	690	890	PF
Reverse Transfer Capacitance	$\text{C}_{\text{rss}}$		-	24	31	PF
<b>Switching Characteristics</b> (Note 4)						
Turn-on Delay Time	$t_{\text{d}(\text{on})}$	$\text{V}_{\text{DD}}=75\text{V}, \text{I}_{\text{D}}=70\text{A}$ $\text{V}_{\text{GS}}=10\text{V}, \text{R}_G=4.7\Omega$	-	26	-	nS
Turn-on Rise Time	$t_r$		-	36	-	nS
Turn-Off Delay Time	$t_{\text{d}(\text{off})}$		-	47	-	nS
Turn-Off Fall Time	$t_f$		-	15	-	nS
Total Gate Charge	$\text{Q}_g$	$\text{V}_{\text{DS}}=75\text{V}, \text{I}_{\text{D}}=70\text{A}, \text{V}_{\text{GS}}=10\text{V}$	-	80	104	nC
Gate-Source Charge	$\text{Q}_{\text{gs}}$		-	32	41	nC
Gate-Drain Charge	$\text{Q}_{\text{gd}}$		-	22	28	nC
<b>Drain-Source Diode Characteristics</b>						
Diode Forward Voltage (Note 3)	$\text{V}_{\text{SD}}$	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_{\text{F}}= \text{I}_{\text{S}}$	-		1.2	V
Diode Forward Current (Note 2)	$\text{I}_{\text{S}}$		-	-	140	A
Reverse Recovery Time	$t_{\text{rr}}$	$\text{T}_J = 25^\circ\text{C}, \text{I}_{\text{F}} = \text{I}_{\text{S}}$ $d\text{i}/dt = 100\text{A}/\mu\text{s}$ (Note 3)	-	146		nS
Reverse Recovery Charge	$\text{Q}_{\text{rr}}$		-	485		nC

**Notes:**


1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board,  $t \leq 10$  sec.
3. Pulse Test: Pulse Width  $\leq 300\mu\text{s}$ , Duty Cycle  $\leq 2\%$ .
4. Guaranteed by design, not subject to production
5. EAS condition :  $\text{T}_J=25^\circ\text{C}, \text{V}_{\text{DD}}=50\text{V}, \text{V}_{\text{G}}=10\text{V}, \text{L}=0.5\text{mH}, \text{R}_G=25\Omega$

## Test Circuit


### 1) E<sub>AS</sub> test Circuit



### 2) Gate charge test Circuit



### 3) Switch Time Test Circuit



### Typical Electrical and Thermal Characteristics




Figure 1 Output Characteristics




Figure 4 Rdson-JunctionTemperature




Figure 2 Transfer Characteristics




Figure 5 Gate Charge




Figure 3 Rdson- Drain Current









Figure 6 Source- Drain Diode Forward


**Figure 7 Capacitance vs Vds**

**Figure 9 Power De-rating**

**Figure 8 Safe Operation Area**

**Figure 10 Current De-rating**

**Figure 11 Normalized Maximum Transient Thermal Impedance**