


GLASS PASSIVATED BRIDGE RECTIFIERS

Features

- ◆ Surge overload rating -210 amperes peak
- ◆ Ideal for printed circuit board
- ◆ Reliable low cost construction utilizing molded plastic technique
- ◆ Plastic material has U/L lammability classification 94V-0

KBJ



Dimensions in inches and (millimeters)

Maximum Ratings And Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Parameter	SYMBOLS	KBJ10005	KBJ1001	KBJ1002	KBJ1004	KBJ1006	KBJ1008	KBJ1010	UNITS
Marking Code									
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum average forward(with heatsink NOTE 2) Rectified current @T _c =100°C(without heatsink)	I <sub(av)< sub=""></sub(av)<>	10 3.0							A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	210							A
Rating for Fusing(t<8.3ms)	I ² _t	183							A ² s
Maximum forward voltage at 5.0A DC Maximum forward voltage at 10.0A DC	V _F	1.0 1.1							V
Maximum DC reverse current T _A =25°C at rated DC blocking voltage T _A =125°C	I _R	10 0.5							μA mA
Typical Junction Capacitance (Note 1)	C _J	55							pF
Typical Thermal Resistance (Note 2)	R _{θJA}	1.4							°C/W
Operating junction temperature range	T _J	-55 to +150							°C
storage temperature range	T _{STG}	-55 to +150							°C

NOTES: 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

2. Device mounted on 75mm*75mm*1.6mm cu plate heatsink.

3. The typical data above is for reference only.

Ratings And Characteristic Curves

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3-TYPICAL JUNCTION CAPACITANCE




FIG.4-TYPICAL FORWARD CHARACTERISTICS





FIG.5-TYPICAL REVERSE CHARACTERISTICS



The curve above is for reference only.