


SURFACE MOUNT TRENCH SCHOTTKY RECTIFIER

Features

- ◆ The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- ◆ Metal silicon junction,majority carrier conduction
- ◆ High efficiency operation
- ◆ Ultra low forward voltage drop,low power losses
- ◆ High forward surge current capability
- ◆ High temperature soldering guaranteed:
260°C/10 seconds,0.375" (9.5mm) lead length, 5 lbs. (2.3kg) tension

DO-214AA/SMB



Dimensions in inches and (millimeters)

Maximum Ratings And Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz,resistive or inductive load,for capacitive load current derate by 20%.

Catalog Number	SYMBOLS	ST34B	ST36B	ST310B	UNITS
Maximum repetitive peak reverse voltage	V _{RRM}	40	60	100	V
Maximum RMS voltage	V _{RMS}	28	42	70	V
Maximum DC blocking voltage	V _{DC}	40	60	100	V
Maximum average forward rectified current 0.375"(9.5mm) lead length(see fig.1)	I _(AV)	3.0			A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	80.0	70.0	80.0	A
Maximum instantaneous forward voltage at 3.0A	V _F	0.45	0.50	0.60	V
Maximum DC reverse current T _A =25 °C	I _R	0.30	0.50	0.3	mA
at rated DC blocking voltage T _A =100 °C		5.0			
Typical junction capacitance (NOTE 1)	C _J	450	400	180	pF
Typical thermal resistance (NOTE 2)	R _{θJA}	60			°C/W
Operating junction temperature range	T _J	-55 to +125	-55 to +150		°C
Storage temperature range	T _{STG}	-55 to +150			°C


Note:1.Measured at 1MHz and applied reverse voltage of 4.0V D.C.

2. Thermal resistance from junction to ambient at 0.375"(9.5mm)lead length,P.C.B. mounted

Ratings And Characteristic Curves

AVERAGE FORWARD RECTIFIED CURRENT,
AMPERES

FIG. 1- FORWARD CURRENT DERATING CURVE



PEAK FORWARD SURGE CURRENT,
AMPERES

FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT





FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS



INSTANTANEOUS REVERSE CURRENT,
MILLIAMPERES

FIG. 4-TYPICAL REVERSE CHARACTERISTICS






FIG. 5-TYPICAL JUNCTION CAPACITANCE



TRANSIENT THERMAL IMPEDANCE,
°C/W

FIG. 6-TYPICAL TRANSIENT THERMAL IMPEDANCE



The curve above is for reference only.